

Slide2Seal is proud to present the new BeadEye<sup>TM</sup> line of products (Pat. No. 62/634,939). The Bead-Eye<sup>TM</sup> products have been developed based on knowledge and expertise of many years, followed by understanding of the customer needs.

The BeadEye™ new range of products is a durable plastic rings located sequentially along narrow tape, which could be Sewn or Welded to a Vinyl / Hail Net / Shade cloth or other fabric.

The product provides a range of innovative solutions for connecting the fabric to any kind of frame or cable in a very quick and efficient way.

## BeadEye™

- Long Life Under Rough Outdoor Conditions
- Significantly Stronger
- Operational Efficiency
- Cost Effective

**Applications** 







## BeadEye™ Technical Data Specifications

The Rings			The state of the s
BE-Trapez10 (Made of POM)	Inside Diameter	10mm	Works with 6mm & 7mm Carabiner
	Thickness	6mm	
	Width	27.8mm	
	High	24.25mm	

The Tape / Webbing					
100% Polyester	Width (B)	On Hand - 35mm / 25mm	Customer Can Choose		
	Thickness	0.70mm			
	Special	Weldable to PVC			

Technical Characteristics

Letteral Strength	100Kg / 220Lb per ring
UV Resistance	KLY 800 (Europe ~ 8yrs)
Color Fastness	4 - 5
Finish Product	
Distance Between Rings (A)	Standard - 50cm / 20" *Customer Can Choose any distance from 20cm / 8" & Up
Other Colors than Black & White	Per agreed MOQ
MOQ	3,000m / 3,300yds Samples up to 30m / 33yds
Weight per 100m / 110Yd.	2.4kg / 5.3Lb.



